

Fork: FOX 36 Float FIT GRIP2 EVOL Factory Kashima 170 mm

Follow FOX 36 recommended settings on the left back side of the casting +10 psi suggested for e-Bike application.

Mondraker recommended FOX 36 FIT GRIP2 fork settings based on Rider weight & All Mountain / Enduro e-MTB application:

SAG		RECOMMENDED SETTING*			
rider weight	air pressure	click(s) from full open			
lbs / kg	psi	HSR	LSR	HSC	LSC
120 / 54	58	1	5-6	1-4	1-3
140 / 64	67	2-3	6-7	3-7	3-5
160 / 73	76	3-4	7-8	6-10	5-7
180 / 82	85	4-5	8-9	9-13	7-9
200 / 91	94	5-6	9-10	12-16	9-11
220 / 100	103	6-7	10-11	15-19	11-13
240 / 109	112	7-8	11-12	18-22	13-15

Suggested fork sag 20%

Rear shock: FOX DPX2 EVOL Factory Kashima

SAG		RECOMMENDED SETTING*	
rider weight	air pressure	click(s) from full open	
lbs / kg	psi	rebound	LSC
120 / 54	120	1	1
140 / 64	140	1-2	1
160 / 73	160	2-3	2
180 / 82	180	3-4	3
200 / 91	200	4-5	4
220 / 100	220	5-6	5
240 / 109	240	6-7	6

** These values offer a general recommendation. Rebound and compression damping settings are a personal choice and should be fine-tuned depending on the riding style and terrain conditions*

Settings based on All Mountain / Enduro e-MTB application & 30-35% recommended sag