

Fork: FOX 36 Float FIT4 EVOL Factory Kashima 170mm

Follow FOX 36 recommended settings on the left back side of the casting.
Mondraker recommended FOX 36 FIT4 fork settings based on Rider weight & Enduro application:

SAG		RECOMMENDED SETTING*	
rider weight	air pressure	clicks from full open	
lbs / kg	psi	rebound	FIT4 compression
120 / 54	55	3-4	1
140 / 64	64	4-5	1
160 / 73	73	5-6	1
180 / 82	82	6-7	2
200 / 91	91	7-8	4
220 / 100	100	8-9	6
240 / 109	109	9-10	8

Suggested fork sag 20%

Rear shock: FOX DHX2 Factory Kashima

Size S: 400lbs **Size M:** 450lbs **Size L/XL:** 500lbs

SAG		RECOMMENDED SETTING*			
rider weight	spring rate	clicks from full open			
lbs / kg	lbs	HSC	LSC	HSR	LSR
120 / 54	400	1	2	1	2
140 / 64	400	2	3	2	3
160 / 73	450	3	4	3	3
180 / 82	450	4	5	3	4
200 / 91	500	5	6	4	5
220 / 100	500	6	7	5	6
240 / 109	500	7	8	6	7

Settings based on Enduro application & 30-35% recommended sag. Add 2-3 clicks each setting for a more controlled "XC-style" ride.

* These values offer a general recommendation. Rebound and compression damping settings are a personal choice and should be fine-tuned depending on the riding style and terrain conditions.