

Fork: FOX 36 Float FIT HSC/LSC EVOL Factory Kashima 160mm

Follow FOX 36 recommended settings on the left back side of the casting +10psi suggested for e-Bike application.
Mondraker recommended FOX 36 Float FIT HSC/LSC EVOL Factory fork settings based on Rider weight & e-MTB application:

SAG		RECOMMENDED SETTING*		
rider weight	air pressure	clicks from full open		
lbs / kg	psi	rebound	HSC	LSC
120 / 54	58	3-4	1-2	1-2
140 / 64	67	4-5	2-3	3-4
160 / 73	76	5-6	3-4	5-6
180 / 82	85	6-7	4-5	7-8
200 / 91	94	7-8	5-6	9-10
220 / 100	103	8-9	6-7	11-12
240 / 109	112	9-10	7-8	12-13

Suggested fork sag 20%

Rear shock: FOX DPX2 EVOL Factory Kashima

SAG		RECOMMENDED SETTING*	
rider weight	air pressure	clicks from full open	
lbs / kg	psi	rebound	LSC
120 / 54	120	1	1
140 / 64	140	1-2	1
160 / 73	160	2-3	2
180 / 82	180	3-4	3
200 / 91	200	4-5	4
220 / 100	220	5-6	5
240 / 109	240	6-7	6

Settings based on e-MTB All Mountain-Enduro application & 30-35% recommended sag.

* These values offer a general recommendation. Rebound and compression damping settings are a personal choice and should be fine-tuned depending on the riding style and terrain conditions.