

**Fork: FOX 40 Float FIT Factory Kashima 200mm**

Follow FOX 40 recommended settings on the left back side of the casting.

Mondraker recommended FOX 40 Float FIT Factory Kashima settings based on Rider weight & Downhill application:

SAG		RECOMMENDED SETTING*		
rider weight	air pressure	clicks from full open		
lbs / kg	psi	rebound	HSC	LSC
120 / 54	49	5-6	1-2	1-2
140 / 64	56	6-7	3-4	2-3
160 / 73	63	7-8	5-6	3-4
180 / 82	70	8-9	7-8	4-5
200 / 91	77	9-10	9-10	5-6
220 / 100	84	10-11	11-12	6-7
240 / 109	91	11-12	13-14	7-8

Suggested fork sag 20%

**Rear shock: FOX DHX2 Factory Kashima**

**Size S:** 450lbs

**Size M:** 500lbs

**Size L/XL:** 550lbs

SAG		RECOMMENDED SETTING*			
rider weight	spring rate	clicks from full open			
lbs / kg	lbs	HSC	LSC	HSR	LSR
120 / 54	450	1	2	3	3
140 / 64	450	2	3	4	4
160 / 73	500	3	4	5	5
180 / 82	500	4	5	5	6
200 / 91	550	5	6	6	7
220 / 100	550	6	7	7	8
240 / 109	550	7	8	8	9

Settings based on Downhill application & 35% recommended sag

\* These values offer a general recommendation. Rebound and compression damping settings are a personal choice and should be fine-tuned depending on the riding style and terrain conditions.